Compact. Robust. Flexible.

Weighing at the Point-of-Sale



Compact

The Ariva-S-Mini's compact design maximizes counter space, benefiting both operators and customers. The smallest counter scale in its class, the Ariva-S-Mini provides the same features as the larger Ariva-S model with a much smaller footprint.



Robust design

Flexibility

Your business depends on checkout scales being ready for use at all times. The Ariva-S-Mini's robust design provides protection against dirt and liquids, for many years of dependable performance.




Ariva-S-Mini

Single and Dual Interval Checkout Scale



The Ariva-S-Mini checkout scales are available in pound (lb), kilogram (kg) or ounce (oz), with various capacities, and your choice of single or dual intervals. These scales are available with RS232 or USB connections.





Sustainable technology

Ariva-S-Mini checkout scales are very conservative when it comes to power consumption. Along with proven longevity, more efficient power supplies and recyclable packaging, Ariva scales are a good business decision with minimal impact on the environment. The Ariva-S-Mini has a robust cast aluminum housing and stainless steel platter. This dual interval scale is the ideal solution for retailers who require both a high capacity, up to 30 lb/15 kg, and a fine weight resolution for light goods.



- Compact smallest footprint in its class
- Single or dual interval weighing in multiple units
- Robust design able to withstand dirt and liquids
- Ideal for environments where accurate weighing is a must
- Easy integration compatible with most POS systems

For the Most Stringent Demands

The Ariva-S-Mini standalone checkout scale is the METTLER TOLEDO checkout solution for retailers with the most stringent demands. The Ariva series for weighing at the register comprises weighing modules to be installed in bioptic scanners (Ariva-B), scales for integration of horizontal scanners (Ariva-H) and standalone scales without scanners (Ariva-S and Ariva-S-Mini).



Ariva-S-Mini shown on top of Ariva-S

Technical data

Ariva-S-Mini Single and Dual Interval Checkout Scales

Weighing ranges

Capacity	Single Interval	Dual Interval
30 lb	30 x 0.01 lb	15 x 0.005 lb / 30 x 0.01 lb
15 lb	15 x 0.005 lb	6 x 0.002 lb / 15 x 0.005 lb
15 kg	15 x 0.005 kg	6 x 0.002 kg / 15 x 0.005 kg
6 kg	N/A	3 x 0.001 kg / 6 x 0.002 kg
240 oz	240 x 0.1 oz	N/A

Interfaces

RS-232 or USB communications for connecting to POS system or cash register. USB communication available as virtual comports with Windows® driver, HID®, or HID® IBM®

POS connectivity

Compatible with most POS systems

Temperature range

 $14^{\circ}F - 104^{\circ}F$ (- $10^{\circ}C - +40^{\circ}C$), 0-85% humidity, non-condensing

Power supply

External 100-240 V AC / 12 VDC / 840 mA power supply

Approvals

OIML, NTEP, CE, NSF, UL

Single display, with base and tower mount options

- Bright, backlit display with energy-saving function
- 5-digit weight display
- Keys for taring and zeroing
- Optional dual display configurations

Device dimensions

- Standard weighing platform: 6.3" x 7.875" (160 mm x 200 mm)
- Minimum height: 2" (50 mm)

www.mt.com/retail _

Height adjustment and leveling with adjustable feet

Further information

Please contact your METTLER TOLEDO system consultant for additional information about the range of services of the Ariva checkout scales as well as optional applications.



ISO 9001 quality management certification
ISO 14001 environmental management certification

For more information