



SECTION D-D
BY METTLER TOLEDO: DRILL TWO #29 HOLES IN
SUPPORT TUBE AND FASTEN DATA PLATE WITH 1/8"
ALUMINUM AB4-4 POP RIVETS.

1. FOUNDATION LENGTH DIMENSION SHOWN IS NOMINAL. ACTUAL TOLERANCE IS -0 +1".
2. MODULE LOCATION DESIGNATION IS USED TO DESIGNATE MODULE ASSEMBLY AND HARDWARE CONFIGURATION.
3. APPLY LOCTITE TO ALL GAP COVER BOLTS.
4. IF CABLE CONNECTORS BECOME CONTAMINATED REMOVE CONTAMINANTS WITH CONNECTOR CLEANER PROVIDED.
5. COUPLER LONGITUDINAL SHIMS MAY BE USED TO CORRECT MISALIGNMENT. A SINGLE 1/8" SHIM SHOULD BE USED AT EACH COUPLER IN THE STANDARD CONFIGURATION.
6. COUPLER VERTICAL SHIMS MAY BE USED IF NECESSARY TO LEVEL MODULES.
7. REFERENCE THE INSTALLATION MANUAL FOR A COMPLETE LISTING OF INSTALLATION PROCEDURES.



1. LOAD CELL BOOT REMOVED FOR CLARITY
2. SIDE COVER WILL BEND IF OVERTIGHTENED!
3. APPLY LOCTITE TO SIDE COVER BOLT AND LOAD CELL PINS
4. MID BASEPLATES WILL USE ONLY 3 ANCHOR BOLTS
5. 1/2" MAXIMUM RECEIVER SHIM HEIGHT

[illegible]