




Dimensions and Locations																			
Model	Capacity	D	D1	D2	H	H1	H2	H3	H4	H5	H6 (a)	L	L1	L2	L3	L4	L5 (a)	W	W1
SLB415	110Kg-220Kg [250lb-500lb]	13.0 [0.51]	22.2 [0.87]	15.9 [0.62]	30.2 [1.19]	1.8 [0.07]	17.3 [0.68]	16.0 [0.63]	4.8 [0.19]	7.9 [0.30]	0.25 [0.010]	133.4 [5.25]	57.7 [2.27]	101.6 [4.00]	25.4 [1.0]	15.4 [0.61]	6.4 [0.25]	30.7 [1.21]	6.1 [0.24]
	550Kg [1100lb]	13.0 [0.51]	22.2 [0.87]	15.9 [0.62]	30.2 [1.19]	1.8 [0.07]	17.3 [0.68]	16.0 [0.63]	4.8 [0.19]	7.9 [0.30]	0.38 [0.015]	133.4 [5.25]	57.7 [2.27]	101.6 [4.00]	25.4 [1.0]	15.4 [0.61]	6.4 [0.25]	30.7 [1.21]	6.1 [0.24]
	1100Kg [2500lb]	13.0 [0.51]	22.2 [0.87]	15.9 [0.62]	30.2 [1.19]	1.8 [0.07]	17.3 [0.68]	16.0 [0.63]	4.8 [0.19]	7.9 [0.30]	0.36 [0.014]	133.4 [5.25]	57.7 [2.27]	101.6 [4.00]	25.4 [1.0]	15.4 [0.61]	6.4 [0.25]	30.7 [1.21]	6.1 [0.24]
	2200Kg [5000lb]	13.0 [0.51]	22.2 [0.87]	15.9 [0.62]	36.6 [1.44]	6.0 [0.24]	22.9 [0.90]	19.6 [0.77]	9.5 [0.37]	12.7 [0.50]	-	136.7 [5.38]	57.9 [2.28]	101.6 [4.00]	25.4 [1.0]	18.4 [0.72]	-	36.8 [1.45]	6.1 [0.24]
	4400Kg [10000lb]	19.3 [0.76]	34.9 [1.38]	22.2 [0.87]	42.9 [1.69]	4.5 [0.18]	29.3 [1.16]	22.6 [0.89]	10.8 [0.42]	17.8 [0.70]	-	171.5 [6.75]	73.8 [2.91]	133.4 [5.25]	38.1 [1.15]	21.4 [0.84]	-	42.9 [1.69]	6.1 [0.24]



CABLE TERMINATION	
+Exc	Green
-Exc	Black
+Sig	White
-Sig	Red
Shield *	Yellow
*Connected to Spring Element	



Notes

1. Dimensions are in mm[INCH].
2. Cable length 2m, 3m, 5m, 10m.
3. Overload stop on 110kg[250lb]-1100kg[2500lb] only.

<input type="radio"/>	Metrology
<input type="radio"/>	Safety
<input type="radio"/>	Ex

[illegible]